



1198.00 EUR
incl. 19% VAT, plus [shipping](#)

- 1366x768 Multi-Touchscreen !
- Fanless ! IP65 Front !
- Intel Kaby Lake CPU !
- 2x LAN, 2x COM !



Support:  [Specifications](#)

D151 series is a 15.6" ultra-thin wide-screen fanless Panel PC featuring Intel Kaby Lake ULV Core-i CPU. The distinct aluminum extrusion frame with matte black or silver finish gives the system an understated luxury and elegant look. The series also featuring a bright TFT-LCD with LED backlight display and true flat 10-point projective capacitive multi-touch front panel that's IP65 compliant, along with optional universal snap-in peripherals (MSR, Smart card reader, NFC/ RFID reader, barcode scanner, camera), making it perfect for diversified self-service and interactive signage markets including retail, hospitality, gaming, corporate, healthcare and light

industrial applications.

| | |
|-------------------------------------|---|
| Model Name | D151-11KS |
| Motherboard | PD11KS |
| Processor | Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible with Skylake 3955U / i3-6100U / i5-6300U / i7-6600U and KabyLake 3965U / i5-7300U / i7-7600U) |
| System Memory | 2 x DDR4 SO-DIMM, support up to 32GB |
| Processor Graphic | Intel® HD Graphics 620 (Graphics Burst Frequency 1.10GHz) |
| Touch Display | |
| LCD Size | 15.6" TFT LCD with LED Backlight 50000 lifetime |
| Brightness | 500nits |
| Resolution | 1366 x 768 |
| Viewing Angle | 170°/160° |
| Touch Screen | True-flat 10 points projective capacitive touch |
| Storage | |
| HDD/SSD | 1 x 2.5 internal HDD/SSD bay |
| Expansion | |
| Extension slots | M.2 (2230) : 1 x M.2 E key for wireless network MiniPCIe : 1 x full length mPCIe supporting mSATA |
| I/O Ports | |
| DC Jack | 1 (8V to 24V wide-range voltage input) |
| USB3.0 | 4 |
| GigaLAN (10/100/1000) | 2 |
| Display-Port (support 4K 3840x2160) | 1 |
| Audio jack | 1 x combo jack w/mic-in and line-out |
| HDMI-out | 1 |
| Serial Port | 1 x RS-232, 1 x RS-232/422/485 |
| Thermal Solution | |
| Thermal Solution | Fanless |
| Audio | |
| Stereo Speaker | 2W x 2 |
| Power | |
| Power Supply | 65W/19V |
| Certification | |
| EMC & Safety | CE/FCC Class A |
| Environment | |
| Operating Temperature | 0°C ~ 40°C (32°F~104°F) |
| Storage Temperature | -20°C ~ 60°C(-4°F~140°F) |
| Relative Humidity | 10%~95% @40°C non-condensing |
| Front Panel Protection | IP65 Compliant |
| Dimension | 400 x 250 x 44 (mm) |
| Weight | 4.8kg (10.58 lb) |
| Mounting | 100mm x 100mm VESA |
| Operating System | win10, linux support by request |