



999.00 EUR

incl. 19% VAT, plus [shipping](#)

- Fanless !
- IP65 Front !
- POE !
- Android !



Support:  [Specifications](#)

- 10.1" 300 nits TFT LCD with LED backlight
- Onboard DDR3L 1333 2GB DRAM
- Onboard 8G Flash ROM
- Strong solid aluminum frame design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Front IP65 for protection against water and dust
- Front bezel meets IP65-rated protection
- Support PoE input
- Jetway also provides 13.3" and 15" Panel PC models, for other sizes please contact sales for more details

| Display | |
|---------------------------------|-----------------------------------------------------|
| Front Bezel | - IP65, NEMA 4 rugged protection, metal front bezel |
| Display Type | - 10.1" With LED Backlight |
| Brightness (cd/m ²) | - 300 nits |
| Display Color | - 262K |
| Resolution | - 1920 x 1200 @ 60Hz |
| Viewing Angle (H/V) | - 140°/140° |
| Pixel Pitch | - 0.03775 x 0.03775 mm |
| Aspect Ratio | - 16:10 |
| Contrast Ratio | - 500:1 |
| Response Time | - 60 ms |
| Touch Screen | |
| Type | - projected capacitive type |
| Active Range | - 257.10 x 159.66mm ±0.2mm |
| Transparency | - ■87% |
| Operating Force | - ■50g |
| Surface Hardness | - ■6H (ASTM D3363, pressure 1N/45°) |
| Operating Temperature | - -10 ~ +60° C |
| CASE | |
| Panel Material | - Aluminum |
| Case Material | - Iron |
| Color | - Black |
| Coating Requirement | - Spray Paint |
| Main System | |
| CPU | - Rock Chip® ARM Cortex A17 1.8GHz/QC |
| RAM | - 2G DDR3L |
| Flash ROM | - 8G Flash ROM |
| Watchdog Timer | - 256 levels, 0~255 sec. |
| Speaker | - 2* 2W/8Ohm |
| OS Support | - Android 5.1 |
| I/O Connector | |
| I/O Ports and Switches | - 1* USB2.0 - 1* OTG - 1* PoE PD |
| PoE | |
| Regulatory Compliance | - IEEE802.3af (PoE) |
| Input Power | - 44~57V |
| Pass Through Data Rates | - 10/100/1000 Mbps |
| Power Consumption | - 8.5W |
| Dimension | |
| Case Dimensions | - 259.3*177.3*34.5mm |
| Certifications | |
| Certifications | - CE, FCC, IP65(Front)-Option |
| Environment | |

| | |
|-----------------|------------------------------------------------------------------------|
| Temperature | - Operating: -10 ~ 50° C - Storage: -20 ~ 60° C |
| Shock | - Operating: 15G■11ms duration |
| Vibration | - Operating: 5~500Hz/1 Grms |
| Warranty | |
| Warranty | - 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty) |