



379.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HB368F21 !

- Intel Elkhart Lake SoC Processor
- 1\* DDR4 3200MHz SO-DIMM up to 32GB
- 2\* USB3.1 (Gen.2), 4\* USB2.0, 2\* RJ45, 1\* Audio (MIC + Line-out), 1\* Line-IN, 3\* DP, 2\* COM, 1\* GPIO
- 160.2\*106\*27 mm
- DC12V\_40W Adapter
- Support TPM2.0 (option)

|                    |                                                                                                                                                                               |  |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Model              | <ul style="list-style-type: none"> <li>– HB368F21-6210-S (non-WiFi)</li> <li>– HB368F21I-6210-S (WiFi)</li> </ul>                                                             |  |
| CPU/Chipset        | – Intel® Elkhart Lake SoC Processor(N6210, TDP 6.5W)                                                                                                                          |  |
| BIOS               | – AMI Flash ROM                                                                                                                                                               |  |
| Memory             | – 1* DDR4 3200MHz SO-DIMM up to 32GB                                                                                                                                          |  |
| Network            | – 2* Realtek RTL8119I GbE                                                                                                                                                     |  |
| Graphics           | <ul style="list-style-type: none"> <li>– Intel® HD Graphics, shared memory</li> <li>– 3* DP (Max Resolution: 4096×2160@60Hz)</li> <li>– Support Triple Displays</li> </ul>    |  |
| Storage            | <ul style="list-style-type: none"> <li>– 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME</li> <li>– 32GB eMMC onboard (option)</li> </ul>                 |  |
| Expansion          | <ul style="list-style-type: none"> <li>– 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)</li> <li>– 1* M.2 B-key (3042, USB3.0 interface)</li> </ul>                      |  |
| Rear Panel I/O     | <ul style="list-style-type: none"> <li>– 2* RJ45</li> <li>– 1* DC in (Lockable)</li> </ul>                                                                                    |  |
| Front Panel I/O    | <ul style="list-style-type: none"> <li>– 1* Power button + Power LED</li> <li>– 4* USB2.0</li> <li>– 1* Audio(Line out+MIC)</li> <li>– 1* Line in</li> <li>– 3* DP</li> </ul> |  |
| Internal Connector | – SIM Card Holder                                                                                                                                                             |  |

|              |                                                                                                                                                                                                                                              |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Source | <ul style="list-style-type: none"> <li>– Adapter : AC 90~240V input / DC12V_40W output</li> <li>– MB : DC12~36V input</li> </ul>                                                                                                             |
| Compliance   | <ul style="list-style-type: none"> <li>– CE, FCC, LVD, RoHS, ErP Ready</li> </ul>                                                                                                                                                            |
| Dimensions   | <ul style="list-style-type: none"> <li>– System: 160.2 (W) x 106 (D) x 27 (H) mm</li> <li>– Net Weight: 0.61KG: Gross Weight: 1.12KG</li> </ul>                                                                                              |
| Temperature  | <ul style="list-style-type: none"> <li>– Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD)</li> <li>– Storage Temperature: -20 ~ 60° C</li> <li>– Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul> |
| OS Support   | <ul style="list-style-type: none"> <li>– Windows 11, Linux</li> </ul>                                                                                                                                                                        |