



119.95 EUR

incl. 19% VAT, plus [shipping](#)

- 15KV ESD protection !
- Ignition control !
- 7x USB3.2 Gen II !
- 600W Surge protection !

7-Port Industrial USB 3.2 Hub with 15KV ESD Protection adds 7 USB 3.2 ports to your system from a single USB port, enabling additional USB device connections. It delivers SuperSpeed USB data transfer rate up to 10Gb/s, offers built-in 15KV ESD protection with over-current detection and protection circuit design. This industrial USB hub also supports 600W power input surge protection on each port to safeguard your connected USB devices and the hub itself from unforeseen power surges, providing smooth and reliable data transferring performance. It is wall and DIN rail-mount supported for easy integration, and its industrial grade rugged metal housing enclosure design allows you to expand your USB capability in harsh industrial environment. Power input range is from 9-24VDC.

#### Features

- Industrial grade rugged metal housing enclosure design to withstand harsh industrial environments
- 7x USB3.2 GENI USB-A port
- Redundant 9VDC to 24VDC power input (optional, Stromversorgung auch über USB Host möglich)
- 15KV ESD USB interface protection
- Power input surge protection (600W) for each port
- Over-current detection and protection circuit design
- Wall and DIN rail mount support
- Supports transfer speed of 5Gbps for USB-A connection
- Supports UASP function (with Windows 8 native USB 3.0 Host driver only)
- Hot-swappable
- LED indicate power and data transfer

#### Specifications

- Chipset: VIA VL813
- Maximum data transfer rate: 5Gbps
- Surge Protection: 600W (max)
- Metal housing with mounting mechanism
- Interfaces/Ports:
- Input: 1, USB 3.2, Type B, Female
- Input: 1, Terminal block (3-Wire)
- Input: 1, DC power adapter jack (power adapter not included)
- Output: 7x USB 3.2, Type A, Female
- Power requirements:
- Input voltage: 9VDC~24VDC
- Product dimensions: 134.4x60x23.7 (L/W/H)
- Product weight: 256g

- Product color: Black
- Environmental conditions:
  - Operating temperature: 0° C to 40° C
  - Operating humidity: 5% to 85% RH
  - Storage temperature: -20° C to 50° C
  - Storage humidity: 5% to 95% RH
- Included USB 3.2 cable:
  - Type B (M) to Type A (M)
  - Length: 6.6 ft (2m)

**Requirements**

- Desktop or notebook with an available USB port (USB 3.2 is recommended)
- Windows® 8/10/11 (32-/64-bit) / 7 (32-/64-bit) / Vista (32-/64-bit) / XP (32-/64-bit) / Server 2003 & 2008 (32-/64-bit) / Server 2008 R2

**Package Contents**

- 7-Port Industrial USB 3.2 Hub with 15KV ESD Protection
- USB 3.2 Type B to Type A cable (2 meters)
- DIN-Rail and wall mount kit
- Terminal block
- Installation guide